

# LIT-1310


Cylindrical, slim projector with built-in track driver for three-circuit track installation. Rotatable and tiltable body for directional lighting. The lower lumen range provides the perfect solution for a more subtle illumination.

## LIT-1310 | Projectors | 3-Circuit Track



H(m)	Diameter(m)	(lx)
1.0	0.33	4685
2.0	0.65	1171
3.0	0.98	521
4.0	1.31	293
5.0	1.63	187

■ Co-C180



Lumen, maintenance & failure rate	L90/B10 >80,000 hrs at 25°C
Body material	Aluminium body powder coating
Dimensions & Weight	H 130mm D 58mm 0.52 kg
Colors	Check colors index
Power supply	Electronic driver
Reflector	Optical Lens
Swivel angles	350° horizontal, 90° vertical

### Customizable on request



\*Longer lead time

Code	LED Lumen	Luminaire Lumen	Efficiency	LED Wattage	Color Temperature	Beam Angle
560921X	1094 lm	960 lm	141.1lm/w	6.8W	3000k	20°
560923X	1094 lm	960 lm	141.1lm/w	6.8W	3000k	36°
560921Y	1148 lm	1006 lm	147.9lm/w	6.8W	4000k	20°
560923Y	1148 lm	1006 lm	147.9lm/w	6.8W	4000k	36°
560221X	1337 lm	1172 lm	134.7lm/w	8.7W	3000k	20°
560223X	1337 lm	1172 lm	134.7lm/w	8.7W	3000k	36°
560221Y	1403 lm	1230 lm	141.3lm/w	8.7W	4000k	20°
560223Y	1403 lm	1230 lm	141.3lm/w	8.7W	4000k	36°
560321X	1724 lm	1511 lm	116.3lm/w	13.0W	3000k	20°
560323X	1724 lm	1511 lm	116.3lm/w	13.0W	3000k	36°
560321Y	1819 lm	1598 lm	123.0lm/w	13.0W	4000k	20°
560323Y	1819 lm	1598 lm	123.0lm/w	13.0W	4000k	36°

Code	White	Black
X	1	7
Y	2	8

### Related Products:

