




LIT-13100

Durable outdoor uplight for in-ground installation. Made of high-quality materials for long-lasting performance. A sleek design that blends seamlessly into any landscape. The smallest solution within this range.

LIT-13100 | Outdoor Uplights | Optical lens



Lumen, maintenance & failure rate	L80/B10 >60,000 hrs at 45°C
Body material	Stainless steel body/frame
Dimensions & Weight	H 56mm D 55mm 0.55 kg
Colors	Stainless steel
Diffuser	Clear glass
Power supply	External 24V DC driver
Reflector	High efficiency optical lens
Driver box	Available upon request

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
3306504	204 lm	144 lm	80.0lm/w	1.8W	3000k	7°
3306505	238 lm	168 lm	93.3lm/w	1.8W	4000k	7°
3306814	410 lm	360 lm	114.3lm/w	3.15W	3000k	19°
3306815	440 lm	386 lm	122.5lm/w	3.15W	4000k	19°
3306824	410 lm	360 lm	114.3lm/w	3.15W	3000k	24°
3306825	440 lm	386 lm	122.5lm/w	3.15W	4000k	24°
3306834	410 lm	360 lm	114.3lm/w	3.15W	3000k	34°
3306835	440 lm	386 lm	122.5lm/w	3.15W	4000k	34°
3306844	410 lm	360 lm	114.3lm/w	3.15W	3000k	50°
3306845	440 lm	386 lm	122.5lm/w	3.15W	4000k	50°

Accessories

Element	IP 67 DRIVER 30W, 24V	
Max.	6 pcs/ Driver	
Code	186633	

Model	2 ways IP connector 3 poles	
IP Rate	IP68	
Code	0100010	

Model	2 ways IP connector 4 poles	
IP Rate	IP68	
Code	0100020	

Model	3 ways IP connector 3 poles	
IP Rate	IP68	
Code	0101010	

Model	3 ways IP connector 4 poles	
IP Rate	IP68	
Code	0101020	