



LIT-13200

Durable outdoor uplight for in-ground installation with a long-lasting performance. A sleek design that blends seamlessly into any landscape. The mid-size solution within this range.

LIT-13200 | Outdoor Uplights | Built-in driver





Lumen, maintenance & failure rate	L80/F50 >60,000 hrs at 45°C
Body material	Stainless steel body/frame
Dimensions & Weight	H 85mm D 80mm 0.73 kg
Colors	Stainless steel
Diffuser	Clear glass
Power supply	Built-in driver
Reflector	High efficiency optical lens

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
3308314	549 lm	396 lm	117.8lm/w	3.36W	3000k	20°
3308315	549 lm	396 lm	117.8lm/w	3.36W	4000k	20°
3308334	549 lm	396 lm	117.8lm/w	3.36W	3000k	36°
3308335	549 lm	396 lm	117.8lm/w	3.36W	4000k	36°
3308354	549 lm	396 lm	117.8lm/w	3.36W	3000k	60°
3308355	549 lm	396 lm	117.8lm/w	3.36W	4000k	60°

LIT-13200

Durable outdoor uplight for in-ground installation with a long-lasting performance. A sleek design that blends seamlessly into any landscape. The mid-size solution within this range.

LIT-13200 | Outdoor Uplights | External driver



Lumen, maintenance & failure rate	L80/B10 >60,000 hrs at 45°C
Body material	Stainless steel body/frame
Dimensions & Weight	H 85mm D 80mm 0.73 kg
Colors	Stainless steel
Diffuser	Clear glass
Power supply	External 24V DC driver
Reflector	High efficiency optical lens
Driver box	Available upon request

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
3309814	585 lm	550 lm	101.8lm/w	5.4W	3000k	15°
3309815	625 lm	588 lm	101.9lm/w	5.4W	4000k	15°
3309834	585 lm	550 lm	101.8lm/w	5.4W	3000k	36°
3309835	625 lm	588 lm	101.9lm/w	5.4W	4000k	36°
3309854	585 lm	550 lm	101.8lm/w	5.4W	3000k	50°
3309855	625 lm	588 lm	101.9lm/w	5.4W	4000k	50°

Accessories

Element	IP 67 DRIVER 30W, 24V	
Max.	6 pcs/ Driver	
Code	186633	

Model	3 ways IP connector 3 poles	
IP Rate	IP68	
Code	0101010	

Model	2 ways IP connector 3 poles	
IP Rate	IP68	
Code	0100010	

Model	3 ways IP connector 4 poles	
IP Rate	IP68	
Code	0101020	

Model	2 ways IP connector 4 poles	
IP Rate	IP68	
Code	0100020	