


LIT-13300


Durable outdoor uplight for in-ground installation with a long-lasting performance. Featuring a stainless steel incline edge frame and aluminum reflector for adjustability.

LIT-13300 | Outdoor Uplights | Recessed



H(m)	Diameter(m)	(lx)
1.0	0.48	12193
2.0	0.96	3048
3.0	1.45	1355
4.0	1.93	762
5.0	2.41	488

■ C0-C180



Lumen, maintenance & failure rate	L80/F10 >55,000 hrs
Body material	Aluminium body powder coating
Dimension	H 153mm D 160mm
Colors	Grey Body with Stainless Steel Ring
Diffuser	Clear glass
Power supply	Included electronic driver
Reflector	High purity aluminium, Adjustable $\pm 15^\circ$

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
3307214	1316 lm	983 lm	109.2 lm/w	9.0W	3000k	14°
3307215	1388 lm	1036 lm	115.1 lm/w	9.0W	4000k	14°
3307314	1724 lm	1287 lm	99 lm/w	13.0W	3000k	14°
3307315	1819 lm	1358 lm	104.5 lm/w	13.0W	4000k	14°
3307224	1316 lm	983 lm	109.2 lm/w	9.0W	3000k	24°
3307225	1388 lm	1036 lm	115.1 lm/w	9.0W	4000k	24°
3307324	1724 lm	1287 lm	99 lm/w	13.0W	3000k	24°
3307325	1819 lm	1358 lm	104.5 lm/w	13.0W	4000k	24°
3307234	1316 lm	983 lm	109.2 lm/w	9.0W	3000k	38°
3307235	1388 lm	1036 lm	115.1lm/w	9.0W	4000k	38°
3307334	1724 lm	1287 lm	99 lm/w	13.0W	3000k	38°
3307335	1819 lm	1358 lm	104.5 lm/w	13.0W	4000k	38°