




LIT-13300

Durable outdoor uplight for in-ground installation with a long-lasting performance. Featuring a stainless steel incline edge frame and aluminum reflector for adjustability.

LIT-13300 | Outdoor Uplights | Recessed



| | |
|-----------------------------------|---|
| Lumen, maintenance & failure rate | L80/F10 >55,000 hrs at 45°C |
| Body material | Aluminium body powder coating |
| Dimensions & Weight | H 153mm D 160mm 1.71 kg |
| Colors | Grey body with stainless steel ring |
| Diffuser | Clear glass |
| Power supply | Included electronic driver |
| Reflector | High purity aluminium, Adjustable ± 15° |

| Code | LED lumen | Luminaire lumen | Efficiency | LED wattage | Color temperature | Beam angle |
|---------|-----------|-----------------|------------|-------------|-------------------|------------|
| 3307214 | 1316 lm | 983 lm | 109.2 lm/w | 9.0W | 3000k | 14° |
| 3307215 | 1388 lm | 1036 lm | 115.1 lm/w | 9.0W | 4000k | 14° |
| 3307314 | 1724 lm | 1287 lm | 99 lm/w | 13.0W | 3000k | 14° |
| 3307315 | 1819 lm | 1358 lm | 104.5 lm/w | 13.0W | 4000k | 14° |
| 3307224 | 1316 lm | 983 lm | 109.2 lm/w | 9.0W | 3000k | 24° |
| 3307225 | 1388 lm | 1036 lm | 115.1 lm/w | 9.0W | 4000k | 24° |
| 3307324 | 1724 lm | 1287 lm | 99 lm/w | 13.0W | 3000k | 24° |
| 3307325 | 1819 lm | 1358 lm | 104.5 lm/w | 13.0W | 4000k | 24° |
| 3307234 | 1316 lm | 983 lm | 109.2 lm/w | 9.0W | 3000k | 38° |
| 3307235 | 1388 lm | 1036 lm | 115.1lm/w | 9.0W | 4000k | 38° |
| 3307334 | 1724 lm | 1287 lm | 99 lm/w | 13.0W | 3000k | 38° |
| 3307335 | 1819 lm | 1358 lm | 104.5 lm/w | 13.0W | 4000k | 38°t |

Accessories

| | | |
|---------|-----------------------------|--|
| Model | 2 ways IP connector 3 poles | |
| IP Rate | IP68 | |
| Code | 0100010 | |

| | | |
|---------|-----------------------------|--|
| Model | 3 ways IP connector 3 poles | |
| IP Rate | IP68 | |
| Code | 0101010 | |

| | | |
|---------|-----------------------------|--|
| Model | 2 ways IP connector 4 poles | |
| IP Rate | IP68 | |
| Code | 0100020 | |

| | | |
|---------|-----------------------------|--|
| Model | 3 ways IP connector 4 poles | |
| IP Rate | IP68 | |
| Code | 0101020 | |

