




LIT-13400

Durable outdoor uplight for in-ground installation with a long-lasting performance. Featuring a stainless steel incline edge frame and aluminum reflector for adjustability. The largest solution within this range.

LIT-13400 | Outdoor Uplights | Recessed



Lumen, maintenance & failure rate	L80/B10 >60,000 hrs at 45°C
Body material	Aluminium body, stainless steel frame
Dimensions & Weight	H 245mm D 260mm 4.50 kg
Colors	Black Body with Stainless Steel Ring
Diffuser	Clear glass
Power supply	Electronic driver
Reflector	High purity aluminium, Adjustable $\pm 15^\circ$

Customizable on request



*Longer lead time

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
3305514	3075 lm	2294 lm	106.2lm/w	21.6W	3000k	20°
3305515	3247 lm	2422 lm	112.1lm/w	21.6W	4000k	20°
3305534	3075 lm	2374 lm	109.9lm/w	21.6W	3000k	34°
3305535	3247 lm	2508 lm	116.0lm/w	21.6W	4000k	34°
3305554	3075 lm	2402 lm	111.2lm/w	21.6W	3000k	60°
3305555	3247 lm	2536 lm	117.4lm/w	21.6W	4000k	60°

Accessories

Model	2 ways IP connector 3 poles	
IP Rate	IP68	
Code	0100010	

Model	3 ways IP connector 3 poles	
IP Rate	IP68	
Code	0101010	

Model	2 ways IP connector 4 poles	
IP Rate	IP68	
Code	0100020	

Model	3 ways IP connector 4 poles	
IP Rate	IP68	
Code	0101020	