

LIT-2200


IP65 waterproof recessed spotlight with a minimal, functional design. Overall diameter of 80mm. Ideal for humid settings like bathrooms.

LIT-2200 | Mellow | Spotlight | Recessed



| H(m) | Diameter(m) | (lx) |
|------|-------------|------|
| 1.0 | 0.77 | 1435 |
| 2.0 | 1.54 | 359 |
| 3.0 | 2.31 | 159 |
| 4.0 | 3.08 | 90 |
| 5.0 | 3.85 | 57 |

■ Co-C180



| | |
|-----------------------------------|--------------------------------|
| Lumen, maintenance & failure rate | L90/B10 >80,000 hrs at 25°C |
| Body material | Aluminium body powder coating |
| Dimensions & Weight | H 95mm D 80mm 0.45 kg |
| Colors | White |
| Diffuser | Clear glass |
| Power supply | Electronic driver |
| Reflector | High purity aluminium |

Customizable on request

Dimmable

Color Temperature

*Longer lead time

| Code | LED Lumen | Luminaire Lumen | Efficiency | LED Wattage | Color Temperature | Beam Angle |
|---------|-----------|-----------------|------------|-------------|-------------------|------------|
| 5661121 | 990 lm | 633 lm | 100.4lm/w | 6.3W | 3000k | 30° |
| 5662121 | 1316 lm | 840 lm | 94.0lm/w | 9.0W | 3000k | 30° |
| 5661122 | 1044 lm | 666 lm | 105.7lm/w | 6.3W | 4000k | 30° |
| 5662122 | 1388 lm | 884 lm | 98.3lm/w | 9.0W | 4000k | 30° |



