



LIT-22200

Light column with a round symmetrical design, robust and durable, it is built to withstand harsh exterior conditions. Used for general outdoor lighting applications.

LIT-22200 | Light Columns



Lumen, maintenance & failure rate	L70/B50 >64,000 hrs at 45°C
Body material	Aluminium body
Dimensions & Weight	Length x D 170mm 24.75 kg
Colors	Dark grey
Diffuser	Clear glass
Power supply	Electronic driver
Reflector	Optical lens

Related Products:



Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Length
4604107	6484 lm	2819 lm	67.1lm/w	42W	3000k	3000mm
4604108	6828 lm	2968 lm	70.6lm/w	42W	4000k	3000mm
4604117	6484 lm	2819 lm	67.1lm/w	42W	3000k	4000mm
4604118	6828 lm	2968 lm	70.6lm/w	42W	4000k	4000mm

H	I	W	EAV	EMIN	Glare index	Classe
4 m	18 m	4 m	12.52 lx	2.46 lx	D3	P2

W	Pathway wideness (m)
I	Poles interdistance (m)
H	Pole height (m)
EAV	Average illuminance
EMIN	Minimum illuminance

	Sidewalk 1 (P2) 72.00 m²	
--	--------------------------	--