



LIT-22300

Light column with an opal cone diffuser emitting light in 360°. Characterized by a unique design aesthetic, it perfectly adapts to any landscape architecture.

LIT-22300 | Light Columns



Lumen, maintenance & failure rate	L70/B50 >60,000 hrs at 45°C
Body material	Aluminium body
Dimensions & Weight	Length x D 160mm 23.80 kg
Colors	Dark grey
Diffuser	Clear PC - opal PC
Power supply	Electronic driver
Reflector	Optical lens

Related Products:



Clear Diffuser

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Length
4606207	3630 lm	2000 lm	79.3lm/w	25.2W	3000k	3500mm
4606208	3630 lm	2000 lm	79.3lm/w	25.2W	4000k	3500mm

Opal Diffuser

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Length
3816127	5606 lm	2845 lm	83.7lm/w	34W	3000k	3500mm
3816128	5827 lm	2957 lm	86.7lm/w	34W	4000k	3500mm
3816107	7488 lm	3800 lm	80.8lm/w	47W	3000k	3500mm
3816108	7888 lm	4003 lm	85.2lm/w	47W	4000k	3500mm

H	I	W	EAV	EMIN	Glare index	Classe
3.5 m	15 m	4 m	11.47 lx	2.16 lx	D5	P2

W	Pathway wideness (m)
I	Poles interdistance (m)
H	Pole height (m)
EAV	Average illuminance
EMIN	Minimum illuminance

	Sidewalk 1 (P2) 60.00 m²	
--	--------------------------	--