

LIT-2310


Fixed recessed round spotlight with compact dimensions and a functional design. Overall diameter of 69mm. Precise accenting, suitable for many different applications and spaces.

LIT-2310 | Mellow | Spotlight | Recessed



H(m)	Diameter(m)	(lx)
1.0	0.70	1530
2.0	1.40	383
3.0	2.11	170
4.0	2.81	96
5.0	3.51	61

■ C0-C180



Lumen, maintenance & failure rate	L90/B10 >80,000 hrs at 25°C
Body material	Aluminium body powder coating
Dimensions & Weight	H 64mm D 69mm 0.22 kg
Colors	White
Diffuser	Clear PC
Power supply	Electronic driver
Reflector	Optical lens

Customizable on request



*Longer lead time

Code	LED Lumen	Luminaire Lumen	Efficiency	LED Wattage	Color Temperature	Beam Angle
6316101	990 lm	809 lm	128.4lm/w	6.3W	3000k	22°
6316201	1316 lm	1075 lm	119.5lm/w	9.0W	3000k	22°
6316121	990 lm	809 lm	128.4lm/w	6.3W	3000k	33°
6316221	1316 lm	1075 lm	119.5lm/w	9.0W	3000k	33°
6316102	1044 lm	853 lm	135.4lm/w	6.3W	4000k	22°
6316202	1388 lm	1134 lm	126lm/w	9.0W	4000k	22°
6316122	1044 lm	853 lm	135.4lm/w	6.3W	4000k	33°
6316222	1388 lm	1134 lm	126lm/w	9.0W	4000k	33°

