

LIT-2410


Adjustable recessed round spotlight with a pivot angle of up to 15° allowing light to be emitted precisely where it is required. With an optical lens for higher efficiency and variety of beam angles. Overall diameter of 100mm.

LIT-2410 | Mellow | Spotlight | Recessed



H(m)	Diameter(m)	(lx)
1.0	0.46	2521
2.0	0.92	630
3.0	1.38	280
4.0	1.83	158
5.0	2.29	101

■ Co-C180



Lumen, maintenance & failure rate	L90/B10 >80,000 hrs at 25°C
Body material	Aluminium body powder coating
Dimensions & Weight	H 112mm D 100mm 0.45 kg
Colors	White
Power supply	Electronic driver
Reflector	Optical lens

Customizable on request

Dimmable

Color Temperature

*Longer lead time



Code	LED Lumen	Luminaire Lumen	Efficiency	LED Wattage	Color Temperature	Beam Angle
5527121	990 lm	800 lm	127.0lm/w	6.3W	3000k	24°
5527221	1316 lm	1063 lm	118.1lm/w	9.0W	3000k	24°
5527321	1724 lm	1393 lm	107.1lm/w	13.0W	3000k	24°
5527122	1044 lm	844 lm	134.0lm/w	6.3W	4000k	24°
5527222	1388 lm	1121 lm	124.5lm/w	9.0W	4000k	24°
5527322	1819 lm	1470 lm	113.0lm/w	13.0W	4000k	24°

Related Products:

LIT-2320



131

