


LIT-2420


Adjustable recessed round spotlight with a pivot angle of up to 15° allowing light to be emitted precisely where it is required. Overall diameter of 151mm. Functional design, the ideal practical solution for illuminating large spaces.

LIT-2420 | Mellow | Spotlight | Recessed



H(m)	Diameter(m)	(lx)
1.0	0.75	5202
2.0	1.51	1301
3.0	2.26	578
4.0	3.01	325
5.0	3.77	208

■ C0-C180



Lumen, maintenance & failure rate	L90/B10 >70,000 hrs
Body material	Aluminum body powder coating
Dimension	H 151mm D 132mm
Colors	White
Diffuser	Clear Glass
Power supply	Electronic Driver
Reflector	High purity aluminum

Customizable on request



*Longer lead time



Code	LED Lumen	Luminaire Lumen	Efficiency	LED Wattage	Color Temperature	Beam Angle
5624621	2700 lm	2000 lm	114.3lm/w	17.5W	3000k	45°
5627621	3143 lm	2330 lm	114.2lm/w	21.3W	3000k	45°
5625621	3588 lm	2657 lm	105.0lm/w	25.3W	3000k	45°
5626621	4617 lm	3420 lm	107.5lm/w	31.8W	3000k	45°
5624622	2851 lm	2111 lm	120.6lm/w	17.5W	4000k	45°
5627622	3318 lm	2460 lm	115.5lm/w	21.3W	4000k	45°
5625622	3788 lm	2808 lm	111.0lm/w	25.3W	4000k	45°
5626622	4848 lm	3590 lm	112.8lm/w	31.8W	4000k	45°

