


# LIT-2520

Fixed recessed square spotlight with a functional design. With an optical lens for higher efficiency and variety of beam angles. Precise accenting, suitable for many different applications and spaces.



| H(m)      | Diameter(m) | (lx) |
|-----------|-------------|------|
| 1.0       | 5.54        | 438  |
| 2.0       | 11.08       | 110  |
| 3.0       | 16.62       | 49   |
| 4.0       | 22.16       | 27   |
| 5.0       | 27.70       | 18   |
| ■ C0-C180 |             |      |



## LIT-2520 | Mellow | Spotlight | Recessed



|                                   |                                |
|-----------------------------------|--------------------------------|
| Lumen, maintenance & failure rate | L90/B10<br>>80,000 hrs at 25°C |
| Body material                     | Aluminium body powder coating  |
| Dimensions & Weight               | 110 x 110 x 94mm 0.45 kg       |
| Colors                            | White                          |
| Power supply                      | Electronic driver              |
| Reflector                         | Optical lens                   |

Customizable on request

 Dimmable





 Color Temperature

\*Longer lead time



| Code    | LED Lumen | Luminaire Lumen | Efficiency | LED Wattage | Color Temperature | Beam Angle |
|---------|-----------|-----------------|------------|-------------|-------------------|------------|
| 5511121 | 990 lm    | 845             | 134.1lm/w  | 6.3W        | 3000k             | 24°        |
| 5511221 | 1316 lm   | 1120 lm         | 124.4lm/w  | 9.0W        | 3000k             | 24°        |
| 5511321 | 1724 lm   | 1465 lm         | 112.7lm/w  | 13.0W       | 3000k             | 24°        |
| 5511122 | 1044 lm   | 860 lm          | 141.2lm/w  | 6.3W        | 4000k             | 24°        |
| 5511222 | 1388 lm   | 1180 lm         | 131.1lm/w  | 9.0W        | 4000k             | 24°        |
| 5511322 | 1819 lm   | 1550 lm         | 119.2lm/w  | 13.0W       | 4000k             | 24°        |

Related Products:

LIT-2610



145

