



LIT-2820

Fixed recessed downlight with a functional design. Overall diameter of 185mm – the mid-size solution within this range. Uniform lighting distribution ideal for general applications.

LIT-2820 | Downlights | Recessed



Lumen, maintenance & failure rate	L80/B10 >70,000 hrs at 25°C
Body material	Aluminium body powder coating
Dimensions & Weight	H 90mm D 185mm 0.85 kg
Colors	White
Diffuser	Opal
Power supply	Electronic Driver
Reflector	White Polycarbonate

Customizable on request



Dimmable



>90 CRI



Color Temperature

*Longer lead time



Code	LED Lumen	Luminaire Lumen	Efficiency	LED Wattage	Color Temperature	Beam Angle
5640541	2700 lm	1676 lm	95.8lm/w	17.5W	3000k	80°
5640542	2851 lm	1768 lm	101.1lm/w	17.5W	4000k	80°
5647541	3143 lm	1950 lm	91.5lm/w	21.3W	3000k	80°
5647542	3318 lm	2060 lm	96.7lm/w	21.3W	4000k	80°



LIT-2820

Fixed recessed downlight with silver reflector. Overall diameter of 185mm – the mid-size solution within this range. Uniform lighting distribution ideal for general applications.

LIT-2820 | Downlights | Recessed



Lumen, maintenance & failure rate	L80/B10 >70,000 hrs at 25°C
Body material	Aluminium body powder coating
Dimensions & Weight	H 90mm D 185mm 0.85 kg
Colors	White
Diffuser	Opal
Power supply	Electronic driver
Reflector	Shining silver

Customizable on request



Dimmable



>90
CRI



Color
Temperature

*Longer lead time

Code	LED Lumen	Luminaire Lumen	Efficiency	LED Wattage	Color Temperature	Beam Angle
5505471	2700 lm	1960 lm	112.0lm/w	17.5W	3000k	80°
5505472	2851 lm	2065 lm	118.0lm/w	17.5W	4000k	80°
5505571	3143 lm	2277 lm	106.9lm/w	21.3W	3000k	80°
5505572	3318 lm	2403 lm	112.8lm/w	21.3W	4000k	80°