



LIT-46100

Fixed recessed outdoor downlight with a functional design that can tolerate challenging weather conditions. Uniform lighting distribution ideal for general applications.



LIT-46100 | Outdoor Downlights | Recessed



Lumen, maintenance & failure rate	L90/B10 >70,000 hrs at 45°C
Body material	Die-cast aluminium body with stainless steel frame
Dimensions & Weight	H 154mm D 220mm 2.64 kg
Colors	Stainless steel
Diffuser	Clear glass
Power supply	Electronic driver
Reflector	High purity aluminium

Customizable on request



*Longer lead time

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
4023024	1724 lm	1050 lm	80.7lm/w	13.0W	3000k	27°
4024024	2700 lm	1645 lm	94.0lm/w	17.5W	3000k	27°
4027024	3143 lm	1915 lm	89.9lm/w	21.3W	3000k	27°
4025024	3588 lm	2185 lm	86.3lm/w	25.3W	3000k	27°
4026024	4617 lm	2812 lm	88.4lm/w	31.8W	3000k	27°
4023025	1819 lm	1108 lm	85.2lm/w	13.0W	4000k	27°
4024025	2851 lm	1736 lm	99.2lm/w	17.5W	4000k	27°
4027025	3318 lm	2020 lm	94.8lm/w	21.3W	4000k	27°
4025025	3788 lm	2307 lm	91.1lm/w	25.3W	4000k	27°
4026025	4848 lm	2953 lm	92.8lm/w	31.8W	4000k	27°

