



LIT-49100

Flexible weatherproof outdoor LED strip perfect for architectural and landscape lighting. Allows for creation of amazing effects through indirect lighting as it tolerates top and side bend.



LIT-49100 | Outdoor flexible LED | Top/Side bend



Lifetime	50,000hrs at 45°C
Body material	Polyurethane and features a white finish
Dimensions & Weight	5000 x 12 x 12mm0.8 kg per 5m
Color	White
Power supply	External 24V DC driver

Customizable on request

Dimmable

*Longer lead time

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Voltage
0911215N	400 lm/m	250 lm/m	50lm/w	5W/M	2700-2900k	24V
0911225N	400 lm/m	250 lm/m	50lm/w	5W/M	3900-4100k	24V
0912215N	800 lm/m	505 lm/m	50.5lm/w	10W/M	2700-2900k	24V
0912225N	800 lm/m	505 lm/m	50.5lm/w	10W/M	3900-4100k	24V



Accessories for Outdoor Flexible LED

Code	Description	
LPV-35-24	IP 67 driver 35w, 24V	
186432	IP 67 driver 75w, 24V	
186433	IP 67 driver 100w, 24V	

Code	Description	
090111	Aluminum profile Dimensions: H 19mm W 14mm	

Code	Description	
090110	Aluminum bracket Dimensions: H 19mm W 14mm	



Code	Description	
0904220	End cap	

Code	Description	
0903220	End cap with cable hole	

Code	Description	
0110010	IP box with 2 cable glands Cable diameter: Input 8-10mm/ output 4-8mm Dimensions: 88x46x30mm	

LIT-49100

Flexible weatherproof outdoor LED strip perfect for architectural and landscape lighting. Allows for creation of amazing effects through indirect lighting as it tolerates top and side bend.



LIT-49100 | Outdoor flexible LED | Top/Side bend

SELV

CRI 90

SDCM 5

IP67

Lifetime	50,000hrs at 45°C
Body material	Polyurethane and features a white finish
Dimensions & Weight	5000 x 16 x 16mm0.8 kg per 5m
Color	White
Power supply	External 24V DC driver

Customizable on request

Dimmable

*Longer lead time

Code	Wave length	Lumen/M	Color temperature	LED wattage	Type
0952235T	RGBW	310lm/m	RGB-Warm	10W/M	Top bend
0952235S	RGBW	310lm/m	RGB-Warm	10W/M	Side bend



Accessories for Outdoor Flexible LED

Code	Description	
LPV-35-24	IP 67 driver 35w, 24V	
186432	IP 67 driver 75w, 24V	
186433	IP 67 driver 100w, 24V	

Code	Description	
0901151	Aluminum profile	

Code	Description	
0902150	Aluminum bracket	

Code	Description	
0904240	End cap	

Code	Description	
0903240	End cap with cable hole	

Code	Description	
0110010	IP box with 2 cable glands Cable diameter: Input 8-10mm/ output 4-8mm Dimensions: 88x46x30mm	

Code	Description	
0908161	Flexible groove	