




LIT-14200

Durable drive over uplight, semi-recessed in-ground installation. Perfect for adding marker lights with optional one or multiple light-emission directions in pathways, walkways, or streetscapes for accenting certain areas.



LIT-14200 | Outdoor Uplights | Recessed



Lumen, maintenance & failure rate	L70/B50 >60,000 hrs at 45°C
Body material	Aluminium & stainless steel cover
Dimensions & Weight	H 125mm D 92mm 0.98 kg
Colors	Stainless steel
Diffuser	Optical lens
Power supply	Electronic driver

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
3300994	316 lm	14 lm	5.8lm/w	2.4W	3000k	1 direction
3300995	323 lm	15 lm	6.3lm/w	2.4W	4000k	1 direction
3301994	316 lm	33 lm	13.8lm/w	2.4W	3000k	2 direction
3301995	323 lm	34 lm	14.2lm/w	2.4W	4000k	2 direction
3302994	316 lm	33 lm	13.8lm/w	2.4W	3000k	3 direction
3302995	323 lm	34 lm	14.2lm/w	2.4W	4000k	3 direction
3303994	316 lm	38 lm	15.8lm/w	2.4W	3000k	4 direction
3303995	323 lm	39 lm	16.3lm/w	2.4W	4000k	4 direction

Accessories

Model	2 ways IP connector 3 poles	
IP Rate	IP68	
Code	0100010	

Model	3 ways IP connector 3 poles	
IP Rate	IP68	
Code	0101010	

Model	2 ways IP connector 4 poles	
IP Rate	IP68	
Code	0100020	

Model	3 ways IP connector 4 poles	
IP Rate	IP68	
Code	0101020	