




LIT-1770

Cylindrical pendant designed for easy and quick installation on magnetic tracks. Slim with a clean aesthetic, it can be suspended at different lengths from the ceiling. An excellent way to add style to modern spaces.

LIT-1770 | Magnetic Pendant Track Light



Lumen, maintenance & failure rate	L80/F10 >55,000 hrs at 25°C
Body material	Aluminium body
Dimensions & Weight	H 200mm D 45mm 0.67 kg per 30cm
Colors	Check colors index
Power supply	Electronic driver
Reflector	Optical lens

Customizable on request



*Longer lead time

Length: 200mm

Code	LED Lumen	Luminaire Lumen	Efficiency	LED Wattage	Color Temperature	Beam Angle
638321X	1100 lm	885 lm	101.7lm/w	8.7W	3000k	15°
638321Y	1125 lm	905 lm	104lm/w	8.7W	4000k	15°
638323X	1100 lm	885 lm	101.7lm/w	8.7W	3000k	36°
638323Y	1125 lm	905 lm	104lm/w	8.7W	4000k	36°
638324X	1100 lm	885 lm	101.7lm/w	8.7W	3000k	50°
638324Y	1125 lm	905 lm	104lm/w	8.7W	4000k	50°
638331X	1442 lm	1160 lm	92lm/w	12.6W	3000k	15°
638331Y	1474 lm	1186 lm	94.1lm/w	12.6W	4000k	15°
638333X	1442 lm	1160 lm	92lm/w	12.6W	3000k	36°
638333Y	1474 lm	1186 lm	94.1lm/w	12.6W	4000k	36°
638334X	1442 lm	1160 lm	92lm/w	12.6W	3000k	50°
638334Y	1474 lm	1186 lm	94.1lm/w	12.6W	4000k	50°

Code	White	Black
X	1	7
Y	2	8

Related Products:

LIT-4420



201

LIT-1770


Cylindrical pendant designed for easy and quick installation on magnetic tracks. Slim with a clean aesthetic, it can be suspended at different lengths from the ceiling. An excellent way to add style to modern spaces.

LIT-1770 | Magnetic Pendant Track Light



H(m)	Diameter(m)	(lx)
1.0	1.55	1517
2.0	3.11	379
3.0	4.66	169
4.0	6.21	95
5.0	7.76	61

■ C0-C180



Lumen, maintenance & failure rate	L80/F10 >55,000 hrs at 25°C
Body material	Aluminium body
Dimensions & Weight	H 300mm D 45mm 0.67 kg per 30cm
Colors	Check colors index
Power supply	Electronic driver
Reflector	Optical lens

Customizable on request



*Longer lead time

Length: 300mm

Code	LED Lumen	Luminaire Lumen	Efficiency	LED Wattage	Color Temperature	Beam Angle
638421X	1100 lm	885 lm	101.7lm/w	8.7W	3000k	15°
638421Y	1125 lm	905 lm	104lm/w	8.7W	4000k	15°
638423X	1100 lm	885 lm	101.7lm/w	8.7W	3000k	36°
638423Y	1125 lm	905 lm	104lm/w	8.7W	4000k	36°
638424X	1100 lm	885 lm	101.7lm/w	8.7W	3000k	50°
638424Y	1125 lm	905 lm	104lm/w	8.7W	4000k	50°
638431X	1442 lm	1160 lm	92lm/w	12.6W	3000k	15°
638431Y	1474 lm	1186 lm	94.1lm/w	12.6W	4000k	15°
638433X	1442 lm	1160 lm	92lm/w	12.6W	3000k	36°
638433Y	1474 lm	1186 lm	94.1lm/w	12.6W	4000k	36°
638434X	1442 lm	1160 lm	92lm/w	12.6W	3000k	50°
638434Y	1474 lm	1186 lm	94.1lm/w	12.6W	4000k	50°

Related Products:

LIT-4420



201

Code	White	Black
X	1	7
Y	2	8