




LIT-28600

Cylindrical wall-mounted luminaire with a single or double light emission option. Simple and minimal design that complements any décor by providing a wash of illumination to a contemporary outdoor façade.

LIT-28600 | Wall lamps | Wall appliques



Lumen, maintenance & failure rate	L90/B10 >80,000 hrs at 45°C
Body material	Die-cast aluminium body
Dimensions & Weight	L 201 x D 100 x W 135mm 1.84 kg
Colors	Dark grey
Diffuser	Clear Glass
Power supply	Electronic driver
Reflector	Optical lens

Related Products:

LIT-46200



403

One direction

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
5223624	1100 lm	737 lm	84.7lm/w	8.7W	3000k	13°
5223724	1100 lm	737 lm	84.7lm/w	8.7W	3000k	24°
5223824	1100 lm	737 lm	84.7lm/w	8.7W	3000k	38°
5223924	1100 lm	737 lm	84.7lm/w	8.7W	3000k	60°
5223625	1388 lm	754 lm	86.6lm/w	8.7W	4000k	13°
5223725	1388 lm	754 lm	86.6lm/w	8.7W	4000k	24°
5223825	1388 lm	754 lm	86.6lm/w	8.7W	3000k	38°
5223925	1388 lm	754 lm	86.6lm/w	8.7W	4000k	60°

Two directions

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
5253154	2x1100 lm	2x737 lm	84.7lm/w	2x8.7W	3000k	13°
5253254	2x1100 lm	2x737 lm	84.7lm/w	2x8.7W	3000k	24°
5253354	2x1100 lm	2x737 lm	84.7lm/w	2x8.7W	3000k	38°
5253554	2x1100 lm	2x737 lm	84.7lm/w	2x8.7W	3000k	60°
5253155	2x1125 lm	2x754 lm	84.7lm/w	2x8.7W	4000k	13°
5253255	2x1125 lm	2x754 lm	84.7lm/w	2x8.7W	4000k	24°
5253355	2x1125 lm	2x754 lm	84.7lm/w	2x8.7W	3000k	38°
5253555	2x1125 lm	2x754 lm	84.7lm/w	2x8.7W	4000k	60°