




LIT-29100

Cuboid wall-mounted luminaire with a single or double light emission option. Simple and minimal design that complements any décor by providing a wash of illumination to a contemporary outdoor façade.

LIT-29100 | Wall lamps | Wall appliques



Lumen, maintenance & failure rate	L90/B50 >70,000 hrs at 45°C
Body material	Aluminium body powder coating
Dimensions & Weight	150 x 150 x 202mm 2.27 kg (one direction) 2.96 kg (two directions)
Colors	Dark grey
Diffuser	Glass
Power supply	Electronic driver
Reflector	Optical lens

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
3701244	2x2700 lm	2x1992 lm	116.3lm/w	2x17.5W	3000k	15°
3701245	2x2851 lm	2x2103 lm	116.3lm/w	2x17.5W	4000k	15°
3703244	2x2700 lm	2x1992 lm	111.2lm/w	2x17.5W	3000k	24°
3703245	2x2851 lm	2x2103 lm	111.2lm/w	2x17.5W	4000k	24°
3705244	2x2700 lm	2x1992 lm	106.9lm/w	2x17.5W	3000k	38°
3705245	2x2851 lm	2x2103 lm	106.9lm/w	2x17.5W	4000k	38°
3707244	2x2700 lm	2x1992 lm	98.6lm/w	2x17.5W	3000k	60°
3707245	2x2851 lm	2x2103 lm	98.6lm/w	2x17.5W	4000k	60°

Related Products:

