



LIT-31100

Wall-mounted luminaire bulkhead with opal diffuser ensuring homogeneous light distribution and visual relaxation, suitable for outdoor applications.

LIT-31100 | Wall lamps | Wall appliques



Lumen, maintenance & failure rate	L80/F10 >72,000 hrs at 45°C
Body material	Die-cast aluminium
Dimensions & Weight	280 x 165 x 95mm0.89 kg
Colors	Black
Diffuser	Polycarbonate Opal diffuser



Customizable on request




*Longer lead time

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
4912557	1360 lm	362 lm	45.2lm/w	8.0W	3000k	Diffuse
4912558	1400 lm	373 lm	46.6lm/w	8.0W	4000k	Diffuse


LIT-31100

Wall-mounted luminaire bulkhead with opal diffuser ensuring homogeneous light distribution and visual relaxation, suitable for outdoor applications.

LIT-31100 | Wall lamps | Wall appliques



Lumen, maintenance & failure rate	L70/B50 >54,000 hrs at 45°C
Body material	Die-cast aluminium
Dimensions & Weight	280 x 165 x 95mm 0.89 kg
Colors	Black
Diffuser	Opal diffuser



Customizable on request



*Longer lead time

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
4930577	3200 lm	920 lm	43.8lm/w	21W	3000k	Diffuse
4930578	3200 lm	920 lm	43.8lm/w	21W	4000k	Diffuse
4940577	3200 lm	1212 lm	57.7lm/w	21W	3000k	Diffuse
4940578	3200 lm	1212 lm	57.7lm/w	21W	4000k	Diffuse
4950577	3200 lm	1546 lm	73.6lm/w	21W	3000k	Diffuse
4950578	3200 lm	1546 lm	73.6lm/w	21W	4000k	Diffuse