


LIT-46400

Surface-mounted cylindrical downlight with toughed clear glass cover featuring a minimal design and a powerful light output. Ideal for outdoor areas such as corridors and roof spaces. The large option within this range.



H(m)	Diameter(m)	(lx)
1.0	0.79	4029
2.0	1.59	1007
3.0	2.38	448
4.0	3.17	252
5.0	3.97	161

■ C0-C180



LIT-46400 | Outdoor Downlights | Surface



Lumen, maintenance & failure rate	L90/B10 >70,000 hrs at 45°C
Body material	Aluminium body powder coating
Dimensions & Weight	H 180mm D 160mm 2.36 kg
Colors	Check color index
Diffuser	Clear glass
Power supply	Electronic driver
Reflector	High purity aluminium

Customizable on request

Color
Temperature

>90
CRI

Dimmable

*Longer lead time



Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
550384X	3588 lm	2175 lm	85.9lm/w	25.3W	3000k	45°
550364X	4617 lm	2800 lm	93.5lm/w	31.8W	3000k	45°
550384Y	3788 lm	2297 lm	90.8lm/w	25.3W	4000k	45°
550364Y	4848 lm	2940 lm	92.4lm/w	31.8W	4000k	45°

Code	White	Dark grey	Black
X	1	4	7
Y	2	5	8

LIT-46400

Surface-mounted cylindrical downlight with toughed clear glass cover featuring a minimal design and a powerful light output. Ideal for outdoor areas such as corridors and roof spaces. The small option within this range.

LIT-46400 | Outdoor Downlights | Surface



Lumen, maintenance & failure rate	L90/B10 >80,000 hrs at 45°C
Body material	Aluminium body powder coating
Dimensions & Weight	H 156mm D 123mm 1.51 kg
Colors	Dark grey
Diffuser	Clear glass
Power supply	Electronic driver
Reflector	High purity aluminium

Customizable on request



*Longer lead time

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
550614X	971 lm	619 lm	98.3lm/w	6.3W	3000k	45°
550624X	1316 lm	840 lm	93.3lm/w	9.0W	3000k	45°
550634X	1745 lm	1112 lm	85.5lm/w	13.0W	3000k	45°
550614Y	1024 lm	653 lm	103.6lm/w	6.3W	4000k	45°
550624Y	1388 lm	885 lm	98.3lm/w	9.0W	4000k	45°
550634Y	1840 lm	1173 lm	90.2lm/w	13.0W	4000k	45°
550644X	2700 lm	1735 lm	99.1lm/w	17.5W	3000k	45°
550644Y	2851 lm	1835 lm	104.8lm/w	17.5W	4000k	45°

Code	White	Dark grey	Black
X	1	4	7
Y	2	5	8