



Adjustable recessed projector with a rotatable and tiltable body. Particularly suitable for projects that require directional lighting with the least possible invasion of space.

LIT-1220 | Projectors | Recessed



H(m)	Diameter(m)	(lx)
1.0	0.49	23911
2.0	0.98	5978
3.0	1.47	2657
4.0	1.95	1494
5.0	2.44	256

■ C0-C180



Lumen, maintenance & failure rate	L90/B10 >70,000 hrs
Body material	Aluminium body powder coating
Dimension	H 146mm D 170mm
Colors	White
Diffuser	Clear glass
Power supply	Electronic Driver
Reflector	High purity aluminium
Replacing model	LIT-3100

Customizable on request



*Longer lead time

Code	LED Lumen	Luminaire Lumen	Efficiency	LED Wattage	Color Temperature	Beam Angle
5654611	2700 lm	2036 lm	116.3lm/w	17.5W	3000k	15°
5654621	2700 lm	2036 lm	116.3lm/w	17.5W	3000k	45°
5657611	3143 lm	2369 lm	111.2lm/w	21.3W	3000k	15°
5657621	3143 lm	2369 lm	111.2lm/w	21.3W	3000k	45°
5655611	3588 lm	2706 lm	106.9lm/w	25.3W	3000k	15°
5655621	3588 lm	2706 lm	106.9lm/w	25.3W	3000k	45°
5656611	4617 lm	3481 lm	109.4lm/w	31.8W	3000k	15°
5656621	4617 lm	3481 lm	109.4lm/w	31.8W	3000k	45°
5654612	2851 lm	2151 lm	122.9lm/w	17.5W	4000k	15°
5654622	2851 lm	2151 lm	122.9lm/w	17.5W	4000k	45°
5657612	3318 lm	2500 lm	115.0lm/w	21.3W	4000k	15°
5657622	3318 lm	2500 lm	115.0lm/w	21.3W	4000k	45°
5655612	3788 lm	2857 lm	112.9lm/w	25.3W	4000k	15°
5655622	3788 lm	2857 lm	112.9lm/w	25.3W	4000k	45°
5656612	4848 lm	3657 lm	115.0lm/w	31.8W	4000k	15°
5656622	4848 lm	3657 lm	115.0lm/w	31.8W	4000k	45°





M

192
NOW

