


LIT-13100


Durable outdoor uplight for in-ground installation. Made of high-quality materials for long-lasting performance. A sleek design that blends seamlessly into any landscape. The smallest solution within this range.

LIT-13100 | Outdoor Uplights | Optical lens



H(m)	Diameter(m)	(lx)
1.0	7.85	16
2.0	15.71	4
3.0	23.56	2
4.0	31.42	1
5.0	39.27	1

■ C0-C180



Lumen, maintenance & failure rate	L80/F50 >60,000 hrs
Body material	Stainless steel body/frame
Dimension	H 70.5mm D 56mm
Colors	Stainless steel
Diffuser	Clear glass
Power supply	External 24V DC driver
Reflector	High efficiency optical lens
Driver box	Available upon request




Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
4116114	410 lm	335 lm	106.3lm/w	3.15W	3000k	20°
4116115	440 lm	362 lm	114.9lm/w	3.15W	4000k	20°



LIT-13100

Durable outdoor uplight for in-ground installation. Made of high-quality materials for long-lasting performance. A sleek design that blends seamlessly into any landscape. The smallest solution within this range.

LIT-13100 | Outdoor Uplights | Frosted glass



Lumen, maintenance & failure rate	L80/B50 >36,000 hrs
Body material	Stainless steel body/frame
Dimension	H 70.5mm D 56mm
Colors	Stainless steel
Diffuser	Frosted glass
Power supply	External 24V DC driver
Driver box	Available upon request

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
4118114	177 lm	35 lm	31.25lm/w	1.12W	3000k	Diffuse
4118115	189 lm	37 lm	33.0lm/w	1.12W	4000k	Diffuse

Accessories

Element	IP 67 DRIVER 30W, 24V	
Max.	6 pcs/ Driver	
Code	186633	

Model	3 ways IP connector 3 poles	
IP Rate	IP68	
Code	0101010	

Model	2 ways IP connector 3 poles	
IP Rate	IP68	
Code	0100010	

Model	3 ways IP connector 4 poles	
IP Rate	IP68	
Code	0101020	

Model	2 ways IP connector 4 poles	
IP Rate	IP68	
Code	0100020	