

LIT-19200


Adjustable projector that can be installed into the ground, wall, or ceiling; with 90° vertical and 30° horizontal rotation, this fixture is the perfect solution for outdoor accent lighting.

LIT-19200 | Outdoor Projectors



H(m)	Diameter(m)	(lx)
1.0	0.21	5002
2.0	0.41	1250
3.0	0.62	556
4.0	0.83	313
5.0	1.04	200

■ C0-C180



Lumen, maintenance & failure rate	L90/B10 >70,000 hrs
Body material	Aluminium body powder coating
Dimension	203 x 100 x 180mm
Colors	Grey
Diffuser	Tempered clear glass
Power supply	Electronic Driver
Reflector	High purity aluminium

Customizable on request



*Longer lead time

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
4444314	1897 lm	1347 lm	113.2lm/w	11.9W	3000k	10°
4444414	2700 lm	1916 lm	109.5lm/w	17.5W	3000k	10°
4444514	3143 lm	2230 lm	104.7lm/w	21.3W	3000k	10°
4444315	2003 lm	1422 lm	119.5lm/w	11.9W	4000k	10°
4444415	2851 lm	2023 lm	115.6lm/w	17.5W	4000k	10°
4444515	3318 lm	2355 lm	110.6lm/w	21.3W	4000k	10°