


# LIT-19300


Adjustable projector that can be installed into the ground using a spike or base. Body designed with 90° vertical rotation, this fixture is the perfect seamless addition to any landscape.

## LIT-19300 | Outdoor Projectors



H(m)	Diameter(m)	(lx)
1.0	0.18	12891
2.0	0.37	3223
3.0	0.55	1432
4.0	0.74	806
5.0	0.92	516

■ Co-C180



Lumen, maintenance & failure rate	L90/B10 >80,000 hrs
Body material	Aluminium body powder coating
Dimension	D 110mm L 212mm
Colors	Dark Grey
Diffuser	Clear glass
Power supply	Electronic Driver
Reflector	High purity aluminium

Customizable on request



\*Longer lead time

### Complete with spike

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
4455214	1316 lm	836 lm	92.9lm/w	9.0W	3000k	10°
4455215	1388 lm	881 lm	97.9lm/w	9.0W	4000k	10°

### Complete with base

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
4465214	1316 lm	836 lm	92.9lm/w	9.0W	3000k	10°
4465215	1388 lm	881 lm	97.9lm/w	9.0W	4000k	10°

