

LIT-19500


Adjustable projector that can be installed into the ground, wall, or ceiling. Contemporary designed round body with 90° vertical rotation, this fixture is the perfect solution for outdoor accent lighting.

LIT-19500 | Outdoor Projectors



H(m)	Diameter(m)	(lx)
1.0	0.43	9187
2.0	0.86	2297
3.0	1.29	1021
4.0	1.71	574
5.0	2.14	367

■ C0-C180



Lumen, maintenance & failure rate	L70/B50 >60,000 hrs
Body material	Aluminium body
Dimension	D 70mm H110mm
Colors	Dark Grey
Diffuser	Tempered clear glass
Power supply	Electronic Driver
Reflector	Optical lens

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
4497214	1100 lm	737 lm	84.7lm/w	8.7W	3000k	13°
4497215	1125 lm	754 lm	86.6lm/w	8.7W	4000k	13°
4497224	1100 lm	737 lm	84.7lm/w	8.7W	3000k	24°
4497225	1125 lm	754 lm	86.6lm/w	8.7W	4000k	24°
4497234	1100 lm	737 lm	84.7lm/w	8.7W	3000k	60°
4497235	1125 lm	754 lm	86.6lm/w	8.7W	4000k	60°