



# LIT-23100

High-performance landscape and urban lighting luminaire with wide-light distribution, ready for all weather conditions with a classic iconic appearance that enhances any setting by giving it an antiquated charm.

## LIT-23100 | Pole top luminaires





Lumen, maintenance & failure rate	L80/B20 >80,000 hrs
Beam angle	90°
Dimension	438 x 438 x 793mm
Colors	Black
Power supply	Electronic Driver
Reflector	Optical lens

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
4212964	4752 lm	3720 lm	109.7lm/w	33.9W	3000k	90°
4212965	4884 lm	3822 lm	112.7lm/w	33.9W	4000k	90°
4213964	7100 lm	5557 lm	111.3lm/w	49.9W	3000k	90°
4213965	7250 lm	5675 lm	113.7lm/w	49.9W	4000k	90°

# LIT-23100

High-performance landscape and urban lighting luminaire with wide-light distribution, ready for all weather conditions with a classic iconic appearance that enhances any setting by giving it an antiquated charm.

## LIT-23100 | Pole top luminaires



Lumen, maintenance & failure rate	L80/B20 >80,000 hrs
Beam angle	Batwing
Dimension	438 x 438 x 793mm
Colors	Black
Power supply	Electronic Driver
Reflector	Optical lens

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
4212664	4752 lm	3895 lm	114.8lm/w	33.9W	3000k	Batwing
4212665	4884 lm	4003 lm	118.0lm/w	33.9W	4000k	Batwing
4213964	7100 lm	5820 lm	116.6lm/w	49.9W	3000k	Batwing
4213965	7250 lm	5943 lm	119.0lm/w	49.9W	4000k	Batwing