



LIT-25100

Durable recessed in wall step light. Made of high-quality materials for long-lasting performance. A sleek design that blends seamlessly into any landscape.

LIT-25100 | Wall lamps | Recessed in-wall





Lumen, maintenance & failure rate	L80/F50 >60,000 hrs
Body material	Stainless steel body/frame
Dimension	H 70.5mm D 56mm
Colors	Stainless steel
Diffuser	Clear glass
Power supply	External 24V DC driver
Reflector	High efficiency asymmetrical optical lens


Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
4753564	410 lm	295 lm	93.6lm/w	3.15W	3000k	Asymmetrical
4753565	440 lm	353 lm	112lm/w	3.15W	4000k	Asymmetrical





Accessories

Element	IP 67 DRIVER 30W, 24V	
Max.	6 pcs/ Driver	
Code	186633	

Model	2 ways IP connector 3 poles	
IP Rate	IP68	
Code	0100010	

Model	2 ways IP connector 4 poles	
IP Rate	IP68	
Code	0100020	

Model	3 ways IP connector 3 poles	
IP Rate	IP68	
Code	0101010	

Model	3 ways IP connector 4 poles	
IP Rate	IP68	
Code	0101020	