


LIT-2610


Adjustable recessed square spotlight with a pivot angle of up to 15° emitting light precisely where it is required. With an optical lens for higher efficiency and variety of beam angles. Overall dimensions of 100x100mm.

LIT-2610 | Mellow | Spotlight | Recessed



| H(m) | Diameter(m) | (lx) |
|------|-------------|------|
| 1.0 | 1.20 | 3916 |
| 2.0 | 2.40 | 979 |
| 3.0 | 3.60 | 435 |
| 4.0 | 4.80 | 245 |
| 5.0 | 6.00 | 157 |

■ C0-C180



| | |
|-----------------------------------|------------------------------|
| Lumen, maintenance & failure rate | L90/B10 >80,000 hrs |
| Body material | Aluminum body powder coating |
| Dimension | 110 x 110 x 103mm |
| Colors | White |
| Power supply | Electronic Driver |
| Reflector | Optical lens |

Customizable on request

Dimmable

Color Temperature

*Longer lead time



| Code | LED Lumen | Luminaire Lumen | Efficiency | LED Wattage | Color Temperature | Beam Angle |
|---------|-----------|-----------------|------------|-------------|-------------------|------------|
| 5528121 | 990 lm | 810 lm | 128.5lm/w | 6.3W | 3000k | 24° |
| 5528221 | 1316 lm | 1077 lm | 119.6lm/w | 9.0W | 3000k | 24° |
| 5528321 | 1724 lm | 1410 lm | 1410lm/w | 13.0W | 3000k | 24° |
| 5528122 | 1044 lm | 855 lm | 855lm/w | 6.3W | 4000k | 24° |
| 5528222 | 1388 lm | 1135 lm | 1135lm/w | 9.0W | 4000k | 24° |
| 5528322 | 1819 lm | 1488 lm | 1488lm/w | 13.0W | 4000k | 24° |

