




Cylindrical wall-mounted luminaire with a single or double light emission option. Simple and minimal design that complements any décor by providing a wash of illumination to a contemporary outdoor façade.

LIT-28600 | Wall lamps | Wall appliques



Lumen, maintenance & failure rate	L90/B10 >80,000 hrs
Body material	Die-cast aluminium body
Dimension	L 201 x D 100 x W 135mm
Colors	Dark grey
Diffuser	Clear Glass
Power supply	Electronic driver
Reflector	Optical lens

Two direction

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
5253154	2x1100 lm	2x737 lm	84.7lm/w	2x8.7W	3000k	13°
5253254	2x1100 lm	2x737 lm	84.7lm/w	2x8.7W	3000k	24°
5253354	2x1100 lm	2x737 lm	84.7lm/w	2x8.7W	3000k	38°
5253554	2x1100 lm	2x737 lm	84.7lm/w	2x8.7W	3000k	60°
5253155	2x1125 lm	2x754 lm	84.7lm/w	2x8.7W	4000k	13°
5253255	2x1125 lm	2x754 lm	84.7lm/w	2x8.7W	4000k	24°
5253355	2x1125 lm	2x754 lm	84.7lm/w	2x8.7W	3000k	38°
5253555	2x1125 lm	2x754 lm	84.7lm/w	2x8.7W	4000k	60°

One direction

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
5223624	1100 lm	737 lm	84.7lm/w	8.7W	3000k	13°
5223724	1100 lm	737 lm	84.7lm/w	8.7W	3000k	24°
5223824	1100 lm	737 lm	84.7lm/w	8.7W	3000k	38°
5223924	1100 lm	737 lm	84.7lm/w	8.7W	3000k	60°
5223625	1388 lm	754 lm	86.6lm/w	8.7W	4000k	13°
5223725	1388 lm	754 lm	86.6lm/w	8.7W	4000k	24°
5223825	1388 lm	754 lm	86.6lm/w	8.7W	3000k	38°
5223925	1388 lm	754 lm	86.6lm/w	8.7W	4000k	60°