




Cuboid wall-mounted luminaire with a single or double light emission option. Simple and minimal design that complements any décor by providing a wash of illumination to a contemporary outdoor façade.

LIT-29100 | Wall lamps | Wall appliques



| | |
|-----------------------------------|-------------------------------|
| Lumen, maintenance & failure rate | L90/B50 >70,000 hrs |
| Body material | Aluminium body powder coating |
| Dimension | 150 x 150 x 202mm |
| Colors | Dark grey |
| Diffuser | Glass |
| Power supply | Electronic driver |
| Reflector | Optical lens |

| Code | LED lumen | Luminaire lumen | Efficiency | LED wattage | Color temperature | Beam angle |
|---------|-----------|-----------------|------------|-------------|-------------------|------------|
| 3701244 | 2x2700 lm | 2x1992 lm | 116.3lm/w | 2x17.5W | 3000k | 15° |
| 3701245 | 2x2851 lm | 2x2103 lm | 116.3lm/w | 2x17.5W | 4000k | 15° |
| 3703244 | 2x2700 lm | 2x1992 lm | 111.2lm/w | 2x17.5W | 3000k | 24° |
| 3703245 | 2x2851 lm | 2x2103 lm | 111.2lm/w | 2x17.5W | 4000k | 24° |
| 3705244 | 2x2700 lm | 2x1992 lm | 106.9lm/w | 2x17.5W | 3000k | 38° |
| 3705245 | 2x2851 lm | 2x2103 lm | 106.9lm/w | 2x17.5W | 4000k | 38° |
| 3707244 | 2x2700 lm | 2x1992 lm | 98.6lm/w | 2x17.5W | 3000k | 60° |
| 3707245 | 2x2851 lm | 2x2103 lm | 98.6lm/w | 2x17.5W | 4000k | 60° |