


LIT-4200


Ceiling-mounted square downlight featuring a minimal design. The low lumen range provides the perfect solution for a more subtle illumination. Ideal for projects with challenging ceiling applications (e.g. concrete, no void).

LIT-4200 | Ceiling Luminaires | Mounted



| H(m) | Diameter(m) | (lx) |
|------|-------------|------|
| 1.0 | 0.60 | 4678 |
| 2.0 | 1.20 | 1169 |
| 3.0 | 1.80 | 520 |
| 4.0 | 2.40 | 292 |
| 5.0 | 3.00 | 187 |

■ C0-C180



| | |
|-----------------------------------|-------------------------------|
| Lumen, maintenance & failure rate | L90/B10 >80,000 hrs |
| Body material | Aluminium body powder coating |
| Dimension | 100 x 100 x 110mm |
| Colors | White |
| Diffuser | Clear PC |
| Power supply | Electronic Driver |
| Reflector | High purity aluminium |

Customizable on request



*Longer lead time

| Code | LED Lumen | Luminaire Lumen | Efficiency | LED Wattage | Color Temperature | Beam Angle |
|---------|-----------|-----------------|------------|-------------|-------------------|------------|
| 5500231 | 1316 lm | 795 lm | 88.3lm/w | 9.0W | 3000k | 36° |
| 5500232 | 1388 lm | 840 lm | 93.3lm/w | 9.0W | 4000k | 36° |