


LIT-49100

Flexible weatherproof outdoor LED strip perfect for architectural and landscape lighting. Allows for creation of amazing effects through indirect lighting as it tolerates top and side bend.

LIT-49100 | Outdoor flexible LED | Top/Side bend



Lifetime	50,000hrs
Body material	Polyurethane and features a white finish
Dimension	5000 x 12 x 12mm
Color	White
Power supply	External 24V DC driver



Customizable on request



*Longer lead time

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Voltage
0911215	400 lm/m	250 lm/m	50lm/w	5w/m	2700-2900k	24V
0911225	400 lm/m	250 lm/m	50lm/w	5w/m	3900-4100k	24V
0912215	800 lm/m	505 lm/m	50.5lm/w	10w/m	2700-2900k	24V
0912225	800 lm/m	505 lm/m	50.5lm/w	10w/m	3900-4100k	24V



LIT-49100

Flexible weatherproof outdoor LED strip perfect for architectural and landscape lighting. Its top bend allows for creation of amazing effects through indirect lighting.

LIT-49100 | Outdoor flexible LED | Top bend



Lifetime	50,000hrs
Body material	Polyurethane and features a white finish
Dimension	5000 x 12 x 12mm
Color	White
Power supply	External 24V DC driver

Customizable on request





*Longer lead time


Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Voltage
0911215T	400 lm/m	250 lm/m	50lm/w	5w/m	2700-2900k	24V
0911225T	400 lm/m	250 lm/m	50lm/w	5w/m	3900-4100k	24V
0912215T	800 lm/m	505 lm/m	50.5lm/w	10w/m	2700-2900k	24V
0912225T	800 lm/m	505 lm/m	50.5lm/w	10w/m	3900-4100k	24V




Accessories for Outdoor Flexible LED

Code	Description	
LPV-35-24	IP 67 driver 35w, 24V	
186432	IP 67 driver 75w, 24V	
186433	IP 67 driver 100w, 24V	

Code	Description	
0901111	Aluminum profile	

Code	Description	
0901110	Aluminum bracket	

Code	Description	
0904220	End cap	

Code	Description	
0903220	End cap with cable hole	