


# LIT-5230


Triple module adjustable recessed spotlight. Pivot angle of up to 15° for precise lighting. The compact size and lower lumen range provides a more subtle illumination. Overall dimensions of 260x100mm.

## LIT-5230 | Rectangular spotlight | Recessed



H(m)	Diameter(m)	(lx)
1.0	0.68	4938
2.0	1.35	1235
3.0	2.03	549
4.0	2.71	309
5.0	3.38	198

■ C0-C180



Lumen, maintenance & failure rate	L90/B10 >80,000 hrs
Body material	Aluminum body powder coating
Dimension	260 x 100 x 75mm
Colors	White
Diffuser	Clear Glass
Power supply	Electronic Driver
Reflector	High purity aluminum

### Customizable on request



\*Longer lead time

Code	LED Lumen	Luminaire Lumen	Efficiency	LED Wattage	Color Temperature	Beam Angle
5681321	3X 990 lm	3X 860 lm	136.5lm/w	3X 6.3W	3000k	36°
5682321	3X 1316 lm	3X 1141 lm	126.8lm/w	3X 9.0W	3000k	36°
5683321	3X 1724 lm	3X 1497 lm	115.2lm/w	3X 13.0W	3000k	36°
5681322	3X 1044 lm	3X 908 lm	144.1lm/w	3X 6.3W	4000k	36°
5682322	3X 1388 lm	3X 1204 lm	133.8lm/w	3X 9.0W	4000k	36°
5683322	3X 1819 lm	3X 1579 lm	121.5lm/w	3X 13.0W	4000k	36°