



LIT-8100

Emergency exit light designed to guide people to safety. Featuring bright highly visible LED lights automatically turned on in the event of a power failure.

LIT-8100 | Exit Sign





Lumen, maintenance & failure rate	L70/B50 >60,000 hrs
Body material	Aluminium body
Dimension	300 x 220 x 60mm
Battery type	LiFePo4, 3.2V, 4.5Ah
Power supply	Electronic Driver







Code	Emergency Time	Charging Time	Output Power (mains operation)	Output Power (Em. operation)	Mounting	Viewing Distance
5101132	3hrs	24hrs	2.1W	2.1W	Ceiling	30m
5102132	3hrs	24hrs	2.1W	2.1W	Wall (Horizontal)	30m
5105132	3hrs	24hrs	2.1W	2.1W	Wall (Vertical)	30m
5104132	3hrs	24hrs	2.1W	2.1W	Suspended	30m
5103132	3hrs	24hrs	2.1W	2.1W	Recessed	30m



Photometric Parameters for Exit Sign	
Uniformity of the illumination= Green / White= 2/10= 0.2	Linear aluminum profile
Contrast= White : Green= 10:1	Ref. (≥5:1 and ≥15:1)
Lgreen ≥240 cd/m ²	
Lwhite ≥38 cd/m ²	

Legends

Code	Description	Dimensions		
0316018	Pictogram ISO Left/Right 30 mm	288x165mm		

Code	Description	Dimensions		
0316019	Pictogram ISO Down/Blank 30mm	288x165mm		

Code	Description	Dimensions		
0316020	Pictogram ISO Down/Down 30 mm	288x165mm		

Code	Description	Dimensions		
0316021	Pictogram ISO Up/Blank 30 mm	288x165mm		

Code	Description	Dimensions		
0316022	Pictogram ISO Up/Up 30 mm	288x165mm	