

# LIT-19350


Adjustable projector that can be installed on surface or ceiling with external electronic driver. Contemporary designed round body with 90° vertical rotation, this fixture is the perfect solution for outdoor accent lighting.

## LIT-19350 | Outdoor Projectors



H(m)	Diameter(m)	(lx)
1.0	0.45	1994
2.0	0.90	499
3.0	1.36	222
4.0	1.81	125
5.0	1.04	80

■ C0-C180



Lumen, maintenance & failure rate	L80/F10 >55,000 hrs at 45°C
Body material	Aluminium body
Dimensions & Weight	D 30mm H 60mm 0.1 kg
Colors	Dark grey
Diffuser	Tempered clear glass
Power supply	External driver 24V
Reflector	Optical lens

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
3405314	177 lm	138 lm	123.2lm/w	1.1W	3000k	10°
3405315	189 lm	147 lm	131.2lm/w	1.1W	4000k	10°
3405324	177 lm	138 lm	123.2lm/w	1.1W	3000k	20°
3405325	189 lm	147 lm	131.2lm/w	1.1W	4000k	20°
3405364	177 lm	138 lm	123.2lm/w	1.1W	3000k	55°
3405365	189 lm	147 lm	131.2lm/w	1.1W	4000k	55°

