

LIT-19600


Adjustable projector that can be installed into the ground, wall, or ceiling. Contemporary designed round body with 90° vertical rotation, this fixture is the perfect solution for outdoor accent lighting.

LIT-19600 | Outdoor Projectors



H(m)	Diameter(m)	(lx)
1.0	0.43	9187
2.0	0.86	2297
3.0	1.29	1021
4.0	1.71	574
5.0	2.14	367

■ C0-C180



Lumen, maintenance & failure rate	L80/B10 >60,000 hrs at 45°C
Body material	Aluminium body
Dimensions & Weight	D 90mm H 200mm 2.30 kg
Colors	Dark grey
Diffuser	Clear glass
Power supply	Electronic driver
Reflector	Optical lens

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
3407424	2700 lm	1834 lm	104.8lm/w	7.5W	3000k	15°
3407425	2851 lm	1937 lm	108.7lm/w	7.5W	4000k	15°
3407444	2700 lm	1834 lm	104.8lm/w	7.5W	3000k	34°
3407445	2851 lm	1937 lm	108.7lm/w	7.5W	4000k	34°
3407464	2700 lm	1834 lm	104.8lm/w	7.5W	3000k	55°
3407465	2851 lm	1937 lm	108.7lm/w	7.5W	4000k	55°
3407524	3178 lm	2159 lm	102.8lm/w	21W	3000k	15°
3407525	3337 lm	2267 lm	108.0lm/w	21W	4000k	15°
3407544	3178 lm	2159 lm	102.8lm/w	21W	3000k	34°
3407545	3337 lm	2267 lm	108.0lm/w	21W	4000k	34°
3407564	3178 lm	2159 lm	102.8lm/w	21W	3000k	55°
3407565	3337 lm	2267 lm	108.0lm/w	21W	4000k	55°