




LIT-37500

High-performance floodlight, featuring high-efficiency LED chips, minimal luminous decay, and pure light color. Perfect for a variety of outdoor applications, ensuring bright and consistent illumination with long-lasting quality.

LIT-37500 | Flood lighting






Lumen, maintenance & failure rate	L80/B50 >90,000 hrs at 45°C
Body material	Steel sheet, electrostatically painted
Dimensions & Weight	L x 270 x 177 mm 7.32 kg per 4 modules
Colors	Dark grey
Diffuser	N/A
Power supply	Electronic driver
Reflector	Optical lens 90°

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Length
3905247	7100 lm	6266 lm	125.6lm/w	50.0W	3000k	201mm
3905248	7250 lm	6398 lm	128.2lm/w	50.0W	4000k	201mm
3906247	14200 lm	12532 lm	125.6lm/w	100.0W	3000k	286mm
3906248	14500 lm	12796 lm	128.2lm/w	100.0W	4000k	286mm
3907247	21300 lm	18798lm	125.6lm/w	150.0W	3000k	371mm
3907248	21750 lm	19194 lm	128.2lm/w	150.0W	4000k	371mm
3908247	28400 lm	25064 lm	125.6lm/w	200.0W	3000k	456mm
3908248	29000 lm	25592 lm	128.2lm/w	200.0W	4000k	456mm

LIT-37500

High-performance floodlight, featuring high-efficiency LED chips, minimal luminous decay, and pure light color. Perfect for a variety of outdoor applications, ensuring bright and consistent illumination with long-lasting quality.

LIT-37500 | Flood lighting



Lumen, maintenance & failure rate	L80/B50 >90,000 hrs at 45°C
Body material	Steel sheet, electrostatically painted
Dimensions & Weight	350 x 560 x 117mm 7.32 kg
Colors	Dark grey
Diffuser	N/A
Power supply	Electronic driver
Reflector	Optical lens 90°

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
3921247	43976 lm	40385 lm	133.3lm/w	303W	3000k	90°
3921248	48264 lm	44322 lm	146.3lm/w	303W	4000k	90°