



LIT-46500

Surface-mounted cubic downlight with a modern compact design, blended with a robust exterior for a bold finish to handle harsh climates.

LIT-46500 | Outdoor Downlights | Surface



Lumen, maintenance & failure rate	L80/F10 >55,000 hrs at 45°C
Body material	Aluminium body powder coating
Dimensions & Weight	H 110mm x 75 x 75 0.45 kg
Colors	Check color index
Diffuser	N/A
Power supply	Electronic driver
Reflector	Optical lens with matt black reflector

Customizable on request

Color

Temperature

>90
CRI

*Longer lead time

Code	LED lumen	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
636731X	1287 lm	890 lm	83.2lm/w	10.7W	3000k	16°
636731Y	1315 lm	910 lm	85.0lm/w	10.7W	4000k	16°
636733X	1287 lm	890 lm	83.2lm/w	10.7W	3000k	40°
636733Y	1315 lm	910 lm	85.0lm/w	10.7W	4000k	40°
636735X	1287 lm	890 lm	83.2lm/w	10.7W	3000k	52°
636735Y	1315 lm	910 lm	85.0lm/w	10.7W	4000k	52°

Code	White	Grey
X	1	4
Y	2	5

Related Products:

LIT-46300



405

