




LIT-49300

Flexible outdoor IP67 wall washer designed for architectural and landscape lighting, featuring a durable aluminum body and secure rubber connections. Uniquely cuttable design allows for customization every three modules (150mm), making it an ideal solution for various lighting applications.



LIT-49300 | Outdoor flexible LED | Side bend



Lumen, maintenance & failure rate	L70/B50 >50,000 hrs at 45°C
Body material	Aluminium
Dimensions & Weight	2400 x 22 x 28.5mm 1.8 kg per 2.4m
Colors	Black
Diffuser	Optical lens
Power supply	Constant voltage 24V DC

Customizable on request

*Longer lead time

Code	Luminaire lumen	Efficiency	LED wattage	Color temperature	Beam angle
0977246	1831 lm	76.3lm/w	24.0W/M	3000k	20°
0977256	1831 lm	76.3lm/w	24.0W/M	4000k	20°
0987246	1831 lm	76.3lm/w	24.0W/M	3000k	45°
0987256	1831 lm	76.3lm/w	24.0W/M	4000k	45°
0997246	1831 lm	76.3lm/w	24.0W/M	3000k	60°
0997256	1831 lm	76.3lm/w	24.0W/M	4000k	60°

Accessories for Outdoor Flexible LED

Code	Description	
1119059	49300, Flexible chain profile Dimensions: 23.2x13.5x1200mm Each reel uses 2 profiles	
Code	Description	
1119060	49300, Fixation bracket Dimensions: 23.2x13.5x50mm	
Code	Description	
1119061	49300, End feed	
Code	Description	
1119062	49300, End cap	
Model	2 ways IP connector 3 poles	
IP Rate	IP68	
Code	0100010	
Model	3 ways IP connector 3 poles	
IP Rate	IP68	
Code	0101010	