


LIT-6100


Recessed panel with flat surface with UGR < 16. Homogeneous illumination for high visual comfort. Ideal for general lighting application in workplaces, healthcare and educational facilities.

LIT-6100 | Lighting Panels | Recessed



H(m)	Diameter(m)	(lx)
1.0	1.86	2362
2.0	3.73	590
3.0	5.59	262
4.0	7.46	148
5.0	9.32	94

■ C0-C180



Lumen, maintenance & failure rate	L80/B10 >72,000 hrs at 25°C
Body material	Steel sheet, electrostatically painted
Dimensions & Weight	596 x 596 x 45mm 3.43 kg
Colors	White
Diffuser	Optical lens
Power supply	Electronic Driver
Reflector	White anti-glare reflector

Customizable on request




*Longer lead time

Code	LED Lumen	Luminaire Lumen	Efficiency	LED Wattage	Color Temperature	Beam Angle
5324671	3540 lm	3126 lm	166.2lm/w	18.8W	3000k	70°
5324681	3743 lm	3305 lm	175.8lm/w	18.8W	4000k	70°
5324691	3653 lm	3226 lm	171.6lm/w	18.8W	6500k	70°
5324071	4920 lm	4345 lm	162.1lm/w	26.8W	3000k	70°
5324081	5210 lm	4601 lm	171.6lm/w	26.8W	4000k	70°
5324091	5080 lm	4486 lm	167.3lm/w	26.8W	6500k	70°

Related Products:

LIT-SYS LA55



51